

**SPRAY FILLER**

- High coverage.
- Excellent filling qualities.
- Wet-to-wet application possible.
- To cover up small uneven parts or irregularities on sanded surfaces.

**General information**

NOVAFILLER is a spray filler with a high coverage that covers up small irregularities. It bonds well on sanded, white or galvanised metals and most synthetic materials. In case of doubt with difficult plastics, treat beforehand with Seal&Bond Special

Primer.

NOVAFILLER is perfect to use for spot repairs and small parts. The adjustable spray head makes this aerosol useable as a spray gun, as the width and flow adjustment is in the head.

**Technical information and packaging**

Colour: Yellow - beige  
 Odour: Specific  
 Vapour pressure at 20 °C: 3500 hPa  
 Density at 20 °C: 0.885 g/cm<sup>3</sup>  
 Solubility in water: None  
 Mixability in water: Poor  
 Organic solvent: 74,9%

EU VOC 662,8 g/l  
 EU VOC in % 74,89%  
 Level of fixed substances: 18,8%  
 Filler strength: +/- 50 microns  
 Storage life: 12 months, dry, cool and frost-free.  
 Safety measures: Please consult the safety data sheet.

**Applications and use**

- the surface to be treated must be grease-free, clean, rust-free and dry;
- shake the aerosol properly for two minutes and try on a test surface;
- let the first coating get absorbed for 12 to 15 minutes before applying a second coating (at 20 °C);
- use NOVAFILLER to finish wall plaster;
- treat difficult plastics first with Seal&Bond Special Primer.

**Product references**

Article nr	Name	Content	Section
120930000	Novafiller	400 ml	surface protection, treatment

