

SPRAY WOOD FILLER WITH HIGH COVERAGE

- Excellent filling qualities.
- Wet-to-wet application possible.
- To fill up pores, nerves and irregularities.

General information

WOODFILLER is a spray finishing filler with a high coverage to cover up small irregularities. Bonds well on sanded wood and derivatives. WOODFILLER is also perfect to use on small,

localised damaged spots. The adjustable nozzle makes this aerosol usable as a spray gun, as it has width and flow adjustment in the head.

Technical information and packaging

Colour: Yellow - beige
 Odour: Specific
 Vapour pressure at 20 °C (68 °F): 3500 hPa (2625 mm Hg)
 Density at 20 °C (68 °F): 0.885 g/cm³.
 Solubility in water: None
 Mixability in water: Poor
 Organic solvent: 74,9%

EU VOC 662,8 g/l
 EU VOC in % 74,89%
 Level of fixed substances: 18,8%
 Filler strength: +/- 50 microns
 Storage life: 12 months, dry, cool and frost-free
 Safety measures: Please consult the safety data sheet

Applications and use

- the surface to be treated must be grease-free, clean, dry and sanded;
- shake the aerosol properly for two minutes and try on a test surface;
- let the first coating absorbed for 12 to 15 minutes before applying a second coating (at 20 °C);
- filling must be done beforehand, as WOODFILLER is be used as a spray finishing filler;
- Treat difficult and oil-absorbent wood types first with Seal&Bond Woodprimer

Product references

Article nr	Name	Content	Section
120935000	Woodfiller	400 ml	surface protection, treatment

