novatio®
innovators in maintenance !

Novatio Europe N.V., Industrielaan 5D, B-2250 Olen,
Tel.: +32-14-25.76.40, Fax: +32-14-22.02.66
europe@novatio.be, www.novatio.com

Easy Cable

❑ simplifies the assembly and disassembly of synthetic materials

❑ safe on any surface

❑ dries quickly and leaves a minimum of residue

❑ effective on all plastic components, with or without sealing rubbers

❑ makes it easier to pull electric cabling trough

APPROVED QUALITY
powered by
novatio®

GENERAL INFORMATION

EASY CABLE is a spray for the assembly and disassembly of any synthetic materials.

EASY CABLE makes it easier to push/pull cables through pipes.

EASY CABLE is applicable anywhere, in the electricity industry as well as for sanitary installations, HVAC, domotics, ...

EASY CABLE is a lubricant for all types of cables.

EASY CABLE will not affect copper conductors. Even on long term the conductors will stay intact.

TECHNICAL INFORMATION

Melting point	: 0°C
Boiling point	: 100°C - 221°C
pH value	: 8
Physical condition	: liquid
Flashpoint	: 70°C
Self-ignition	: 255°C
Colour	: transparent-white

PACKAGING

Aerosol 400ml   Article number 233985000

novatio.com

INSTRUCTIONS FOR USE

- Shake well before use.
- Spray directly onto the cable or into the pipe.
- Act immediately.

APPLICATIONS

- makes it easier to push/pull cabling through pipes
- thin cables in thick bundles for domotics and telephony break easily under severe strain
- in case of coaxial cables, the central core breaks under severe strain
- in the residential and industrial construction industry, for both new and renovated properties, stiff wiring is difficult to pull through pipes; even a draw spring occasionally poses problems
- the pre-flexible cable is easier to pull through cable ducts
- makes it easier to install rubbers in verandas & greenhouses, easy to remove on glass
- to assemble and disassemble PVC pipes, with or without rubbers, in sanitary installations
- to assemble and disassemble bicycle tyres
- makes it easier to assemble solar collectors
- to assemble oil seals