

Butalu



- very high immediate adhesiveness
- very high tear resistance
- adheres to most materials



GENERAL INFO

BUTALU is a sealing tape which consists of a modified butyl rubber body, a complex aluminium support reinforced with synthetic material, and a silicon protective film.

Due to the unique composition of the butyl rubber mass, a very high initial adhesion is obtained. The extreme flexible rubber mass adapts itself to each form and fills smoothly irregularities in the surface.

The aluminium support is reinforced with synthetic material and is therefore tear resistant, unalterable and extremely weatherproof.

BUTALU allows sealing of leaks or finishing off of joints in a quick and very effective way.

TECHNICAL INFO

Thickness	: +/- 0.7 mm
Aluminium support	: complex aluminium film reinforced with synthetic material
Adhesive mass	: modified butyl rubber cold adhesive
Specific weight	: 1100 g/m ²
Peeling force on fireproof cement	: at 90°C and 200 mm/min >= 10 N/cm
Temperature resistance	: -30°C to +100°C
Application temperature	: +5°C to +40°C
Chemical resistance	: water : excellent : weather conditions : excellent : hydrocarbons : not resistant
Shelf life	: cool and dry - minimum 1 year
Safety measures	: please consult the MSDS (material safety data sheet)

PACKAGING

Roll 10 m x 50 mm	Art.nr. 603059000
Roll 10 m x 100 mm	Art.nr. 603259000
Roll 10 m x 150 mm	Art.nr. 603159000
Abbreviation	BLU

603059000-PI-Butalu-EN-061002-P1/2

APPLICATIONS

- sealing roof joints at:
 - gutter - zinc - lead
 - domes
 - chimneys
 - feed-through pipes
 - grates
 - lead flashings
- sealing pipe connections in ventilation, airco, heating systems
- sealing glass or polycarbonate in veranda and greenhouse construction
- thermal insulation and corrosion protection in pipelines
- sealing and bonding of hinged or moving connections
- sealing leaks in waste pipes

INSTRUCTIONS FOR USE

- Surfaces have to be dry and free from grease and dust.
- Porous surfaces have to be stabilized with an appropriate primer.
- Cut off BUTALU at the desired length.
- Remove the protective film gradually.
- Press BUTALU strongly, preferably with a press-on roll. Remove air inclusion.
- When joining BUTALU together, always overlap for at least 5 cm.
- When applying between 0°C and 5°C, always check if the surfaces are free from ice and condensation.

603059000-PI-Butalu-EN-061002-p2/2

All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Novatio makes no warranties as to the accuracy of completeness of the information, and disclaims any liability regarding its use. Novatio's only obligations are those in the Standard terms and conditions of Sale for this product, and in no case will Novatio be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product.