



# Clear-Lube

- unique adhesive properties
- excellent penetration
- has a clean, transparent overspray



## GENERAL INFO

CLEAR-LUBE is a specially formulated lubricant, based on acrylic copolymers and neutral, synthetic oils, mixed with aliphatic and some aromatic oil derivatives, in order to increase the running-in effect. CLEAR-LUBE contains PTFE in order to increase the life span and to reduce the sliding resistance.

CLEAR-LUBE has been formulated to offer a high lubrication capacity at high pressure and in difficult conditions.

CLEAR-LUBE both protects against corrosion because of the formation of a thin polymer film, and penetrates deeply into the objects that have to be lubricated.

CLEAR-LUBE can be used in a wide temperature range, without any change of viscosity. Due to its high adhesive capacity, CLEAR-LUBE is resistant to high-pressure cleaning. CLEAR-LUBE reduces chain friction and wear and extends chain life up to 10 fold.

CLEAR-LUBE is safe to use with rubbers and synthetic materials.

## TECHNICAL INFO

Specific weight	: 0.885
Solid substances	: approx. 30%
Temperature range	: -25°C until +300°C
Viscosity	: on application: 48sec. - B6 FLOW cup : after evaporation of solvent: 6 min. 6 sec. - B6 Flow cup
Basis	: acrylic - copolymers is neutral oil
Solvent	: aliphatic hydrocarbons with some aromatics
Additives	: PTFE

## PACKAGING

Aerosols 400 ml	Art.nr. 214001000
Abbreviation	CLB

## APPLICATIONS

- has been formulated for indoor and outdoor heavy duty lubrication
- extremely effective on intermittent and inaccessible lubrication points
- is suitable for most types of industry, typically on chains, conveyors, open gears, wire-rope, cables, joints, linkages, lead screws, hinges, locking mechanisms
- effective on rubber "O"-ring chains
- is particularly useful where equipment has to withstand severe conditions such as outdoor exposure or contact with acids, alkalis, hot & cold water and steam

## INSTRUCTIONS FOR USE

- Shake before use.
- Keep the spray can always upright.
- In order to obtain optimal results, the previous lubricants should first be removed with Novatio Kleenspray-S.

214001000-PI-Clear-Lube-EN-060804-P2/2

All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Novatio makes no warranties as to the accuracy of completeness of the information, and disclaims any liability regarding its use. Novatio's only obligations are those in the Standard terms and conditions of Sale for this product, and in no case will Novatio be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product.