



# Multi Super 5

- 5 innovations in one product
- displaces water and moisture
- protects against corrosion
- cleans mechanical parts, including plastic and rubber
- strong and fast penetration



## GENERAL INFORMATION

MULTI SUPER 5 provides a high capillary effect and good creeping action. It penetrates into the smallest cavities causing a chemical attack which loosens the rust.

MULTI SUPER 5 contains no silicones or graphite.

## TECHNICAL INFORMATION

Specific weight	: 0,811 at 20°C
Flash point	: 52°C
Boiling point	: 116°C
Solidity point	: none until -62°C
Viscosity	: 2 Cps at 38°C
Dielectrical constant	: 33 KV min/215 mm (ASTMD-877)
Lubrication capacity	: more than 226 kg (Falex step test)
Shelf life	: 12 months

## APPLICATIONS

MULTI SUPER 5 is a very universal product. It can be used in all types of industry, to:

- release jammed screws, bolts and nuts, pipe fittings and joints
- displace moisture from ignition contacts and electrical leads, and protects them
- lubricate and clean brake linkages, cables and all kinds of chains
- protect metal surfaces from corrosion

## PACKAGING

Aerosol 400 ml	Art. number 232001000
Drum 5 L	Art. number 232002000

Abbreviation MS5

232001000-PI-Multi Super 5-EN-070206-P1/1

All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Novatio makes no warranties as to the accuracy or completeness of the information, and disclaims any liability regarding its use. Novatio's only obligations are those in the Standard terms and conditions of Sale for this product, and in no case will Novatio be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product.