

# Seal & Bond Trimfix WT



- ideal for bonding large surfaces
- for permanent or non-permanent bondings
- spray pattern is variable



## GENERAL INFORMATION

Seal & Bond Trimfix WT is a High-Tech spray adhesive in aerosol based on synthetic rubber.

Seal & Bond Trimfix WT is a professional spray adhesive, that is marked by its special web-technology (WT). Through the combination of the adhesive and the special spray nozzle it can be sprayed in a web-structure, which has very good results on rough surfaces.

Seal & Bond Trimfix WT has a wide range of applications.

Seal & Bond Trimfix WT bonds durable and gives connections a high strength.

Seal & Bond Trimfix WT is ideal where spraying equipment, a brush or other application techniques can't be used.

Seal & Bond Trimfix WT has a high immediate adhesive power.

## TECHNICAL DATA

Basis	: synthetic rubber in a mixture of organic solvents
Specific weight	: 0,8 kg/litre
Solid materials	: 15 % +/- 1%
Colour	: yellow-transparent
Drying time	: max. 3 minutes
Open working time	: between 10 and 60 minutes
Temperature resistance	: 50°C constant - peak: 100°C
Consumption	: 5 to 6 m <sup>2</sup> for a light connection
Packaging	: aerosol 400 ml
Shelf life	: in a closed packing 1 year at +/- 18°C
Cleaning agent	: Novatio Safety Clean
Spray width is variable	: from +/- 2,5 cm till 12 cm

## PACKAGING

Aerosol 400 ml      Article n° 511002000

## INSTRUCTIONS FOR USE

- Shake the aerosol well before use.
- Spray on a clean, dry, dust-free and degreased surface from a distance of 20 to 25 cm.

### 1. NON-PERMANENT BONDING

- Apply a thin layer on the part to be bonded, let evaporate for a moment and join together. This bond can be removed without damaging the surfaces.

### 2. PERMANENT BONDING

- On non-porous materials and foams: apply a smooth layer on both surfaces. Wait for 2 to 5 minutes and join together.
- Important : porous materials might need a second layer.
- This aerosol has a rotatable spray nozzle in 3 positions : L=Low, M=Medium, H=High.



**KEEP THE AEROSOL UPSIDE DOWN AFTER USE AND SPRAY TILL THE ADHESIVE VAPOUR STOPS !!!**

## APPLICATIONS

- Seal & Bond Trimfix WT is suited for bonding paper, textile, cardboard, foams, polyurethane foam, cork, polystyrene, felt, vinyl, plastics, reproductions, glass fibre,... to each other or to glass, metal, wood, ceramics, concrete, plastering, fibre plate, ...
- Seal & Bond Trimfix WT can be used in :
  - covering sector or related sectors
  - textile-covering-furniture-interior design
  - stand construction, car repair, packaging, labelling, ...
- not suited for the bonding of P.V.C.films

*Attention : Seal & Bond Trimfix WT is not suited for applications above 50°C where peeling forces occur.*

511002000-PI-Trimfix-EN-060511-P2/2

All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Novatio makes no warranties as to the accuracy of completeness of the information, and disclaims any liability regarding its use. Novatio's only obligations are those in the Standard terms and conditions of Sale for this product, and in no case will Novatio be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product.