

Sanding Indicator

SIN

DETECTS IRREGULARITIES IN FILLER, PRIMER, AND SPRAY FILLER AFTER SANDING

- Quick drying acrylic.
- Fine and equal spray mist.
- Does not stick to sand paper.
- Matte look: better visibility of lower placed parts.

General information

SANDING INDICATOR is the perfect product to detect sanded spots and irregularities when using filler, primer or spray filler. The particularly

fine spray mist produces an equal coating that is essential for good results. With its matte look, one can see the lower placed parts much better.

Technical information and packaging

Basis: Acrylic
 Colour: Black
 Odour: Solvent
 Filler strength: +/- 50 microns
 Vapour pressure at 20 °C: 300 hPa
 Density at 20 °C: 0.94 g/cm³.
 Solubility in water: None
 Mixability in water: Poor

EU-VOC 828,0 g/l.
 Thermal resistance: 90 °C
 VOC value: 257,5 g
 Safety measures: Please consult the safety data sheet.

Applications and use

- Shake the aerosol properly for two minutes and try on a test surface
- To be used on a dry surface
- After use, turn the aerosol around and empty to keep the spray head clean

Product references

Article nr	Name	Content	Section
120301000	Sanding Indicator	400 ml	surface protection, treatment

