



Novarroof

- can be used on moist surfaces
- does not harden, remains flexible
- is guaranteed for 20 years



GENERAL INFORMATION

NOVAROOF is a sealant with a unique composition. Due to the combination of bitumes, butyl rubber and glass fibres, a product with a very high tensile strength and flexibility is obtained.

Therefore, a life span of 20 years is guaranteed for NOVAROOF.

NOVAROOF can be applied on most surfaces, also in a moist condition.

TECHNICAL DATA

Composition	: modified bitumes, glass fibres and butyl rubber
Elongation at rupture (dry film)	: 170%
Temperature resistance	: -45°C to +85°C
U.V. resistance	: excellent
Ageing properties	: none during 20 years
Water resistance	: very good in case of a normal draining
Climatic resistance	: excellent
Resistance to hydrocarbons	: non resistant
Application temperature	: -12°C to +50°C
Consumption	: 750 g/m ² on smooth surfaces : 1,9 kg/m ² on rough surfaces
Safety measures	: please consult the MSDS (safety data sheet)

CAUTION: DO NOT APPLY ON SNOW OR GLAZE ICE !!!

PACKAGING

Cartridges 310 ml	Article number 602106000
Pots 10 kg	Article number 602210000

Abbreviation NRF

APPLICATIONS

NOVAROOF can be applied on most building materials such as: brick, concrete, wood, lead, copper, tin, bituminous roofing materials, galvanized steel, insulation materials, PVC, polyester.

TYPICAL APPLICATIONS:

- all types of roof repairs: sloping and flat roofs, roof gutters, edgings, drain pipes, lead flashings, corrugated plates, also on wet surfaces
- sealing and finishing off of roof joints, eaves, feedtrough ducts, chimneys
- as cold adhesive for roof repairs with bituminous roofing materials
- making waterproof of concrete and brickwork in foundations and terraces
- corrosion protection of underground pipelines and channels

INSTRUCTIONS FOR USE

- The surface has to be solid and clean.
- Remove loose parts and hardened bitumes.
- Cut open blisters in roofing materials in a crossshaped way.
- Larger repairs have to be reinforced with pieces of roofing or glass fibre tissue.
- Apply with a cartridge gun, brush or spatula.
- Finish off and clean tools with Novatio Safety Clean.

602106000-PI-Novarof-EN-070731-P2/2

All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Novatio makes no warranties as to the accuracy or completeness of the information, and disclaims any liability regarding its use. Novatio's only obligations are those in the Standard terms and conditions of Sale for this product, and in no case will Novatio be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product.